

ML-180 TORTILLA MACHINE WITH SPEED DRIVE

DATA SHEET

MAIN SPECIFICATIONS

POWER SUPPLY:	220 VCA 60Hz	Two phase motor
MOTORS:	2HP - 2 HP	
ELECTRICAL CONSUMPTION:	3.9 kW/h	
GAS CONSUMPTION:	12.1 m ³ /h - natural gas 4.7 m ³ /h - LP gas (vaporized)	
CALORIFIC VALUE:	430,000 BTU/h	
GAS TYPE:	Natural and LP	
MINIMUM LP GAS PRESSURE:	14 PSI=lb/in ²	
WEIGHT:	950 kg	

PRODUCTION CAPABILITY

TORTILLA SIZE:	10 to 16 cm
KILOS PER HOUR:	From 90kg to 180kg*

Note: The diameter of the tortilla depends on the cutter used

*Depending on temperature, dough texture, etc.

*50Hz frequency 380V available

Improvements:

- Speed drive to raise or lower production without need for a modification.
- Maintenance free 2HP sealed sumitomo geared motor.

Main features:

- Low operational cost
- Reinforced transmissions
- Thermal treatment in sprockets
- Stainless steel thermal covers
- Industrial gear reducer



COMPONENTS:

- Head Unit
- Bench
- Cooking oven
- Tortilla receiver
- Speed drive

Product features:

- Excellent cooking
- High quality tortillas
- Produces normal tortilla and taco tortilla

