

ML-30 TORTILLA MACHINE

DATA SHEET

MAIN SPECIFICATIONS

POWER SUPPLY:	220 VCA 60Hz Two-phase motor*
MOTORS:	2HP - ¼ HP
ELECTRICAL CONSUMPTION:	1.9 kW/h
GAS CONSUMPTION:	2.3 m³/h - natural gas 0.9 m³/h - LP gas (vaporized)
CALORIFIC VALUE:	82,550 BTU/h
GAS TYPE:	Natural and LP
MINIMUM LP GAS PRESSURE:	7 PSI=lb/in²
WEIGHT:	373 kg

PRODUCTION CAPABILITY

TORTILLA SIZE:	10 to 16 cm
TORTILLAS PER HOUR:	Up to 1550*

Note: The diameter of the tortilla depends on the cutter used

*Depending on temperature, dough texture, etc.

*50Hz frequency 380V available

Main features:

- Produces 26 tortillas per minute*
- Saves space
- Saves labor
- Saves on gas and electricity
- Easy maintenance oven
- Low operational cost
- Reinforced transmissions
- Thermal treatment in sprockets
- Stainless steel thermal covers
- Industrial gear reducer



COMPONENTS:

- Head Unit
- Bench
- Cooking oven
- Tortilla receiver

Product features:

- Excellent cooking
- High quality tortillas
- Produces normal tortilla and taco tortilla

