

MLR-30 TORTILLA MACHINE

DATA SHEET

MAIN SPECIFICATIONS

POWER SUPPLY: 220 VCA 60Hz Two-phase motor

MOTORS: 1HP - ¼ HP

ELECTRICAL CONSUMPTION: 1.1 kW/h

GAS CONSUMPTION: 2.3 m³/h - natural gas
0.9 m³/h - LP gas (vaporized)

CALORIFIC VALUE: 82,550 BTU/h

GAS TYPE: Natural and LP

MINIMUM LP GAS PRESSURE: 7 PSI=lb/in²

WEIGHT: 373 kg

PRODUCTION CAPABILITY

TORTILLA SIZE: 10 to 20 cm

TORTILLAS PER HOUR: Up to 1440*

Note: The diameter of the tortilla depends on the cutter used

*Depending on temperature, dough texture, etc.

*50Hz frequency 380V available

Main features:

- Produces 24 tortillas per minute*
- Saves space
- Saves labor
- Saves on gas and electricity
- Easy maintenance oven
- Low operational cost
- Thermal treatment in sprockets
- Industrial gear reducer
- Single piece complete kit



COMPONENTS:

- Head Unit
- Bench
- Cooking oven
- Tortilla receiver

Product features:

- Safety solenoid valve
- Electronic ignition (Optional)
- Teflon griddle (Optional)
- Excellent cooking
- High quality tortillas
- Versatility on size and shape

